

ARKOSLIGHT®



WIRE TRIMLESS
A C C E S S O R Y



WIRE TRIMLESS ACCESSORY

SUSPENSION ACCESSORIES


WIRE TRIMLESS ACCESSORY

Wire Trimless Accessory umfasst eine Reihe von Zubehörteilen, um Spanner und Kabel der Arkoslight Pendelleuchten direkt an der Decke ohne sichtbare Deckendosen oder Befestigungselemente zu installieren. Dadurch wird eine minimalistische und optisch saubere Umsetzung im Raum erzielt.

Mit Wire Trimless Accessory werden die an der Decke anliegenden Elemente des Standardprodukts (Deckendosen, Befestigungselemente, Treiberboxen...) durch eine einfache Einbauanwendung verborgen.


Wire Trimless Accessory sorgt für unauffällige Installation und eine äußerst minimalistische Ästhetik. Die Kabel kommen als Teil der Struktur aus der Decke. Dieses Detail sorgt für ein besonders nüchternes und essentielles Erscheinungsbild, insbesondere bei Kombinationen von mehreren Elementen.








- (A) Mains Trimless
- (B) Mains Thick Trimless
- (C) Coaxial Trimless
- (D) Unipolar Trimless
- (E) Steel Cable Trimless
- (F) Steel Cable Regulator Trimless



VERFÜGBAR FÜR:



ART



SALT



VOLA



BRIGIT



ALASKA




SPIN



HOLLY



DRUM SUSPENSION



LINE SUSPENSION



STICK



SCOPE



BLACK FOSTER SUSPENSION




SLIMGOT




FIFTY+ SUSPENSION



MINIMAL TRACK



TRACK 48V SUSPENSION



BLACK FOSTER CUSTOM SURFACE



BLACK FOSTER CUSTOM SUR. MICRO



		P	CCT	I	Flux	LOR
ART	A342-00-10- WT NT BC BG	6,3W	2700K	700mA	570Lm	92%
	A342-00-11- WT NT BC BG	6,3W	3000K	700mA	630Lm	92%
	A342-00-20- WT NT BC BG	6,3W	2700K	700mA	570Lm	92%
	DALI* A342-00-21- WT NT BC BG	6,3W	3000K	700mA	630Lm	92%

220
240 V~ |  IP20 | CRI>90 | L80B10
>60.000 h

* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



FINISHING**	Lamp	Base
	WT  WT 	
	NT  NT 	
	BC  WT 	
	BG  WT 	



BASE NOT USED WITH WIRE TRIMLESS
INSTALLATION.

OPTIONAL ACCESSORY

WIRE TRIMLESS Accessory

Unipolar Trimless A023-00-04- | W | N |

2 Pcs. needed



COLOUR | WT  | NT  | BC  | BG  | W  | N  | MATERIAL |  BR |  ABS+PC |

OTHER CCT | ** OTHER FINISHING COMBINATIONS » PLEASE CONSULT

» PLEASE CONSULT

UNIPOLAR TRIMLESS





Arklight Headquarters, Valencia (Spain) | Francesc Rifé Studio | Víctor García Martínez Arquitecto | Photography: David Zarzoso



		P	CCT	I	Flux	LOR
ART Direct & Indirect	A343-00-10- WT NT BC BG	6,3W	2700K	700mA	570Lm	92%
	A343-00-11- WT NT BC BG	6,3W	3000K	700mA	630Lm	92%
	A343-00-20- WT NT BC BG	6,3W	2700K	700mA	570Lm	92%
	A343-00-21- WT NT BC BG	6,3W	3000K	700mA	630Lm	92%

220
240 V~

IP20

CRI>90

L80B10
>60.000h

MacAdam
Step 3

INCL

2 X Ø50

UGR <19

38°

* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

FINISHING**	Lamp	Base
	WT	WT
	NT	NT
	BC	WT
	BG	WT

BASE NOT USED WITH WIRE TRIMLESS
INSTALLATION.

OPTIONAL ACCESSORY

WIRE TRIMLESS Accessory



Unipolar TrimlessA023-00-04- | W | N |

2 Pcs. needed

REMOTE

INCL

Ø20




COLOUR | WT | NT | BC | BG | W | N | MATERIAL | BR | ABS+PC |

OTHER CCT | ** OTHER FINISHING COMBINATIONS » PLEASE CONSULT

» PLEASE CONSULT

UNIPOLAR TRIMLESS





		P	CCT	I	Flux	LOR
ART Modular 3	WT NT BC BG	6,3W	2700K	700mA	570Lm	92%
	WT NT BC BG	6,3W	3000K	700mA	630Lm	92%
	 WT NT BC BG	6,3W	2700K	700mA	570Lm	92%
	 WT NT BC BG	6,3W	3000K	700mA	630Lm	92%
ART Modular 4	WT NT BC BG	8,4W	2700K	700mA	760Lm	92%
	WT NT BC BG	8,4W	3000K	700mA	840Lm	92%
	 WT NT BC BG	8,4W	2700K	700mA	760Lm	92%
	 WT NT BC BG	8,4W	3000K	700mA	840Lm	92%
ART Modular 5	WT NT BC BG	10,5W	2700K	700mA	950Lm	92%
	WT NT BC BG	10,5W	3000K	700mA	1050Lm	92%
	 WT NT BC BG	10,5W	2700K	700mA	950Lm	92%
	 WT NT BC BG	10,5W	3000K	700mA	1050Lm	92%

220
240 V~ |  IP20 | CRI>90 | L80B10
>60.000h

* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



FINISHING**	Lamp	Base
	WT ☐	WT ☐
	NT ☐	NT ☐
	BC ☐	WT ☐
	BG ☐	WT ☐


BASE NOT USED WITH WIRE TRIMLESS
INSTALLATION.

OPTIONAL ACCESSORY


WIRE TRIMLESS Accessory

Unipolar Trimless A023-00-04- | W | N |

2 Pcs. needed




UNIPOLAR TRIMLESS





COLOUR | WT ☐ | NT ☐ | BC ☐ | BG ☐ | W ☐ | N ☐ | MATERIAL |  BR |  ABS+PC |

OTHER CCT | ** OTHER FINISHING COMBINATIONS » PLEASE CONSULT


((())) » PLEASE CONSULT




Direct & Indirect Option



Direct & Indirect Option



Direct & Indirect Options



ACHTUNG

Art Modular '3' hat eine Länge von 800 mm.
Die vorhandenen Versionen von Art sind
1000 mm lang.

ALASKA



		P	CCT	I	Flux	LOR
ALASKA Big	A455- 00 -0- 00 -0- N BG	8,4W	2700K	500mA	1040Lm	37%
	A455- 00 -0- 00 -1- N BG	8,4W	3000K	500mA	1100Lm	37%

220
240 V~

IP20

CRI>90

L90B10
> 60.000 h

MacAdam
Step 2

OPTIONS*

INCL

44°

		P	CCT	I	Flux	LOR
ALASKA Big Wire Trimless	A455- 00 -1- 00 -0- N BG	8,4W	2700K	500mA	1040Lm	37%
	A455- 00 -1- 00 -1- N BG	8,4W	3000K	500mA	1100Lm	37%

220
240 V~

IP20

CRI>90

L90B10
> 60.000 h

MacAdam
Step 2

INCL

Ø20

INCL

44°



00	CORD LENGTH - L
0	2 m
1	3 m
2	5 m

00	OPTIONS*
2	DIM DALI
5	DIM Phase Cut

FINISHING*	Lamp	Base
	N ■ NT ■	
	BG ■ NT ■	


OPTIONAL ACCESSORIES

CORD Accessory	0223-00-00- N
Included 1 unit x lamp	



COLOUR | N ■ | BG ■ | NT ■ | MATERIAL | AL | OPTICAL GLASS |

OTHER CCT & DIM OPTIONS PLEASE CONSULT | * OTHER FINISHING COMBINATIONS PLEASE CONSULT



		P	CCT	I	Flux	LOR
ALASKA	A425- -0-10- N BG	4,5W	2700K	500mA	475Lm	30%
	A425- -0-11- N BG	4,5W	3000K	500mA	500Lm	30%
	A425- -0-20- N BG	4,5W	2700K	500mA	475Lm	30%
	A425- -0-21- N BG	4,5W	3000K	500mA	500Lm	30%

220
240

V~

IP20

|

CRI>90

|

L80B10
> 60.000h

MacAdam
Step 2

INCL

Ø50

21°

	CORD LENGTH - L
0	2 m
2	5 m



Other length please consult

FINISHING*	Lamp	Base
	N	NT
	BG	NT

BASE NOT USED WITH WIRE TRIMLESS
INSTALLATION.


OPTIONAL ACCESSORIES

CORD Accessory
0223-00-00- N



WIRE TRIMLESS Accessory

Coaxial Trimless
A023-00-03- W N



COLOUR | N | NT | BG | W | MATERIAL | AL | OPTICAL GLASS |

OTHER CCT & DIM OPTIONS PLEASE CONSULT | * OTHER FINISHING COMBINATIONS PLEASE CONSULT » PLEASE CONSULT

WIRE TRIMLESS ACCESSORY


STICK



OPTIONAL ACCESSORIES

CORD Accessory


0223-00-00- | N |



WIRE TRIMLESS Accessory

Coaxial Trimless

A023-00-03- | W | N |



COAXIAL TRIMLESS




		P	CCT	Beam	I	Flux	LOR
STICK	A40- ○ - ∞ - ∞ -10- WT NT MG	5,6W	2700K	22°	500mA	530Lm	84%
	A40- ○ - ∞ - ∞ -11- WT NT MG	5,6W	3000K	22°	500mA	600Lm	84%
	A40- ○ - ∞ - ∞ -20- WT NT MG	5,6W	2700K	37°	500mA	530Lm	82%
	A40- ○ - ∞ - ∞ -21- WT NT MG	5,6W	3000K	37°	500mA	600Lm	82%
	A40- ○ - ∞ - ∞ -30- WT NT MG	5,6W	2700K	46°	500mA	530Lm	81%
	A40- ○ - ∞ - ∞ -31- WT NT MG	5,6W	3000K	46°	500mA	600Lm	81%

220 V~ | IP20 | CRI>90 | L80B10 > 60.000 h | MacAdam Step 2 | OPTIONS* | INCL | Ø50 | 22° / 37° / 46°

		P	CCT	Beam	I	Flux	LOR
STICK Base	A50- ○ - ∞ - ∞ -10- WT NT MG	5,6W	2700K	22°	500mA	530Lm	84%
	A50- ○ - ∞ - ∞ -11- WT NT MG	5,6W	3000K	22°	500mA	600Lm	84%
	A50- ○ - ∞ - ∞ -20- WT NT MG	5,6W	2700K	37°	500mA	530Lm	82%
	A50- ○ - ∞ - ∞ -21- WT NT MG	5,6W	3000K	37°	500mA	600Lm	82%
	A50- ○ - ∞ - ∞ -30- WT NT MG	5,6W	2700K	46°	500mA	530Lm	81%
	A50- ○ - ∞ - ∞ -31- WT NT MG	5,6W	3000K	46°	500mA	600Lm	81%

220 V~ | IP20 | CRI>90 | L80B10 > 60.000 h | MacAdam Step 2 | OPTIONS* | INCL | 22° / 37° / 46°

○	STICK LENGTH	∞	CORD LENGHT-L	∞	OPTIONS*
4	STICK 22 220 mm	0	2 m	2	DIM DALI
5	STICK 44 440 mm	2	5 m	5	DIM Phase Cut
6	STICK 66 660 mm				



COLOUR | WT | NT | MG | W | N | MATERIAL | AL | ABS+PC |

» PLEASE CONSULT

HOLLY



		P	CCT	Beam	I	Flux	LOR
HOLLY	A281- Ⓞ -0-00- WT NT MC MG	2,1W	2700K	19°	700mA	190Lm	90%
	A281- Ⓞ -0-01- WT NT MC MG	2,1W	3000K	19°	700mA	210Lm	90%
	A281- Ⓞ -0-10- WT NT MC MG	2,1W	2700K	38°	700mA	190Lm	92%
	A281- Ⓞ -0-11- WT NT MC MG	2,1W	3000K	38°	700mA	210Lm	92 %


220
240 V~ |  IP20 | CRI>90 | L80B10
>60.000 h



Ⓞ	CORD LENGTH - L
0	2 m
1	3 m
2	5 m


FINISHING **	Lamp	Base
WT	WT  W 	
NT	NT  N 	
MC	MC  N 	
MG	MG  N 	

BASE NOT USED WITH WIRE TRIMLESS
INSTALLATION.




OPTIONAL ACCESSORIES

CORD Accessory
0223-00-00- W N



WIRE TRIMLESS Accessory

Coaxial Trimless
A023-00-03- W N



COLOUR | WT  | NT  | MC  | MG  | W  | N  | MATERIAL |  AL |  ABS |


* DIM OPTIONS PLEASE CONSULT | ** OTHER FINISHING COMBINATIONS PLEASE CONSULT

 » PLEASE CONSULT


SCOPE



MAINS TRIMLESS



STEEL CABLE
REGULATOR TRIMLESS



								P	CCT	I	Flux	LOR
SCOPE 35	A261-30-00-	WW	WG	WR	NN	NG		7W	2700K	200mA	910Lm	89%
	A261-30-01-	WW	WG	WR	NN	NG		7W	3000K	200mA	940Lm	89%
	A261-30-02-	WW	WG	WR	NN	NG		7W	4000K	200mA	960Lm	89%

220
240 V~

IP20

CRI>90

L80B10
> 60.000 h

MacAdam
Step 2

PHASE CUT

INCL

CABLE
2 m

FAST

47°

								P	CCT	I	Flux	LOR
SCOPE 27	A261-20-00-	WW	WG	WR	NN	NG		7W	2700K	200mA	910Lm	89%
	A261-20-01-	WW	WG	WR	NN	NG		7W	3000K	200mA	940Lm	89%
	A261-20-02-	WW	WG	WR	NN	NG		7W	4000K	200mA	960Lm	89%

220
240 V~

IP20

CRI>90

L80B10
> 60.000 h

MacAdam
Step 2

PHASE CUT

INCL

CABLE
2 m

FAST

47°

								P	CCT	I	Flux	LOR
SCOPE 21	A261-10-00-	WW	WG	WR	NN	NG		7W	2700K	200mA	910Lm	89%
	A261-10-01-	WW	WG	WR	NN	NG		7W	3000K	200mA	940Lm	89%
	A261-10-02-	WW	WG	WR	NN	NG		7W	4000K	200mA	960Lm	89%

220
240 V~

IP20

CRI>90

L80B10
> 60.000 h

MacAdam
Step 2

INCL

CABLE
2 m

FAST

47°

OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Mains Trimless	A023-00-01-	W	N
----------------	-------------	---	---

Ø15

REMOTE

INCL

Ø20

MIN.35

FASTENING

Steel Cable Regulator Trimless

A023-00-06-	W	N
-------------	---	---

Ø15

INCL

Ø20

MIN.20

COLOUR | WW | WG | WR | NN | NG | W | N | MATERIAL | AL | PC |

OTHER COLOURS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

WIRE TRIMLESS ACCESSORY

VOLA SUSPENSION



		P	CCT	I	Flux	LOR
VOLA Suspension	A442-00- ① -0- WT NT	19W	2700K	500mA	3080Lm	80%
	A442-00- ① -1- WT NT	19W	3000K	500mA	3160Lm	80%
	A442-00- ① -2- WT NT	19W	4000K	500mA	3320Lm	80%

220
240 V~

IP20

CRI>90

L80B10
> 60.000 h

MacAdam
Step 2

OPTIONS*

INCL

CABLE
2 m

FAST

119°

①	*OPTIONS
1	No DIM
2	DIM DALI
3	DIM Push
5	DIM Phase Cut

OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Mains Thick Trimless


A023-00-02- | W | N |



FASTENING

Steel Cable Trimless

A023-00-05- | W | N | 3 Pcs. needed



COLOUR | WT ☐ | NT ☒ | W ☐ | N ☒ | MATERIAL | AL | PC |

* OTHER DIM OPTIONS PLEASE CONSULT » PLEASE CONSULT

WIRE TRIMLESS ACCESSORY

SALT



MAINS TRIMLESS



MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS



											P	CCT	I	Flux	LOR
SALT 3	A220-03-	1 -0-	WW	WG	WR	NW	NG	NR			22W	2700K	700mA	2800Lm	79%
	A220-03-	1 -1-	WW	WG	WR	NW	NG	NR			22W	3000K	700mA	3025Lm	79%
	A220-03-	1 -2-	WW	WG	WR	NW	NG	NR			22W	4000K	700mA	3075Lm	79%
SALT 4	A220-04-	⊙ -1-	WW	WG	WR	NW	NG	NR			27W	3000K	700mA	4100Lm	79%
	A220-04-	⊙ -2-	WW	WG	WR	NW	NG	NR			27W	4000K	700mA	4175Lm	79%
SALT 5	A220-05-	⊙ -1-	WW	WG	WR	NW	NG	NR			35W	3000K	900mA	5125Lm	79%
	A220-05-	⊙ -2-	WW	WG	WR	NW	NG	NR			35W	4000K	900mA	5225Lm	79%
SALT 6	A220-06-	⊙ -1-	WW	WG	WR	NW	NG	NR			47,5W	3000K	1200mA	6550Lm	79%
	A220-06-	⊙ -2-	WW	WG	WR	NW	NG	NR			47,5W	4000K	1200mA	6650Lm	79%

220
240 V~ | IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 2 OPTIONS* INCL CABLE 2 m FAST 77°

											P	CCT	I	Flux	LOR
SALT PC 3	A220-03-	1 -0-	TW	TN							22W	2700K	700mA	2800Lm	84%
	A220-03-	1 -1-	TW	TN							22W	3000K	700mA	3025Lm	84%
	A220-03-	1 -2-	TW	TN							22W	4000K	700mA	3075Lm	84%
SALT PC 4	A220-04-	⊙ -1-	TW	TN							27W	3000K	700mA	4100Lm	84%
	A220-04-	⊙ -2-	TW	TN							27W	4000K	700mA	4175Lm	84%
SALT PC 5	A220-05-	⊙ -1-	TW	TN							35W	3000K	900mA	5125Lm	84%
	A220-05-	⊙ -2-	TW	TN							35W	4000K	900mA	5225Lm	84%
SALT PC 6	A220-06-	⊙ -1-	TW	TN							47,5W	3000K	1200mA	6550Lm	84%
	A220-06-	⊙ -2-	TW	TN							47,5W	4000K	1200mA	6650Lm	84%

220
240 V~ | IP20 | CRI>90 | L80B10 >60.000 h


MacAdam Step 2 OPTIONS* INCL CABLE 2 m FAST 91°

⊙ *OPTIONS

2	DIM Push
4	DIM DALI

PHASE CUT PLEASE CONSULT

SALT & SALT PC



COLOUR | WW | WG | WR | NW | NG | NR | MATERIAL | AL | PMMA |

COLOUR | TW | TN | W | N | MATERIAL | AL | PC | PMMA | » PLEASE CONSULT


OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED


Mains Trimless NO DIM
A023-00-01- | W | N |

Mains Thick Trimless DIM
A023-00-02- | W | N |



FASTENING

Steel Cable Trimless
A023-00-05- | W | N | 3 Pcs. needed





									P	CCT	I	Flux	LOR
SALT Mini	A280-00-10-	WW	WG	WR	NW	NG	NR		10W	2700K	700mA	1300Lm	67%
	A280-00-11-	WW	WG	WR	NW	NG	NR		10W	3000K	700mA	1400Lm	67%
	A280-00-12-	WW	WG	WR	NW	NG	NR		10W	4000K	700mA	1425Lm	67%

220
240

V~

IP20

CRI>90

L80B10
> 60.000 h

MacAdam
Step 2

PHASE CUT

INCL

2 m

FAST

80°




OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Mains Trimless A023-00-01- | W | N |



FASTENING

Steel Cable Trimless A023-00-05- | W | N |



COLOUR | WW | WG | WR | NW | NG | NR | MATERIAL | AL | PMMA |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

» PLEASE CONSULT

MAINS TRIMLESS



STEEL CABLE TRIMLESS




BRIGIT



		P	CCT	I	Flux	LOR
BRIGIT	0900-60-01- W	27W	3000K	700mA	4100Lm	88%
	0900-60-02- W	27W	4000K	700mA	4175Lm	88%
	0900-60-01- O	27W	3000K	700mA	4100Lm	42%
	0900-60-02- O	27W	4000K	700mA	4175Lm	42%
	0900-60-01- R	27W	3000K	700mA	4100Lm	30%
	0900-60-02- R	27W	4000K	700mA	4175Lm	30%

220
240 V~ |  IP20 | CRI>90 | L80B10 >60.000 h



BRIGIT White



BRIGIT Orange




BRIGIT Red

OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED


Mains Thick Trimless A023-00-02- | W | N |



FASTENING

Steel Cable Trimless A023-00-05- | W | N |

4 Pcs. needed



COLOUR | W  | O  | R  | W  | N  | MATERIAL |  PE |  PC |

» PLEASE CONSULT

WIRE TRIMLESS ACCESSORY

DRUM SUSPENSION



		P	CCT	I	Flux	LOR
DRUM 90 Suspension	A358-20- -1- WT NT	119W	3000K	700mA	16100Lm	87%
	A358-20- -2- WT NT	119W	4000K	700mA	16350Lm	87%

220
240 V~ | IP20 | CRI>90 | L80B10
> 60.000 h

MacAdam
Step 2

OPTIONS*

INCL

CABLE
2 m

FAST

96°

		P	CCT	I	Flux	LOR
DRUM 70 Suspension	A358-10- -1- WT NT	59,5W	3000K	700mA	8050Lm	87%
	A358-10- -2- WT NT	59,5W	4000K	700mA	8175Lm	87%

220
240 V~ | IP20 | CRI>90 | L80B10
> 60.000 h

MacAdam
Step 2

OPTIONS*

INCL

CABLE
2 m

FAST

96°

	*OPTIONS
2	DIM DALI
3	DIM 1-10 V

OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED


Mains Thick Trimless

A023-00-02- | W | N |

REMOTE

INCL

Ø20



FASTENING


Steel Cable Trimless

A023-00-05- | W | N |



4 Pcs. needed

INCL



Ø20



DRUM 90 SUSPENSION



DRUM 70 SUSPENSION



COLOUR | WT | NT | W | N | MATERIAL | AL | PMMA |

» PLEASE CONSULT

WIRE TRIMLESS ACCESSORY

LINE SUSPENSION



Photography: Nom Bureau




OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Coaxial Trimless


A023-00-03- | W | N |



FASTENING

Steel Cable Trimless

A023-00-05- | W | N |



COAXIAL TRIMLESS



STEEL CABLE TRIMLESS



		P	CCT	I	Flux	LOR
LINE Suspension 1500	A436-10- ② -0- WT NT	31,5W	2700K	1050mA	4500Lm	61%
	A436-10- ② -1- WT NT	31,5W	3000K	1050mA	4800Lm	61%
	A436-10- ② -2- WT NT	31,5W	4000K	1050mA	4950Lm	61%
LINE Suspension 2000	A436-20- ② -0- WT NT	42W	2700K	1400mA	6000Lm	61%
	A436-20- ② -1- WT NT	42W	3000K	1400mA	6400Lm	61%
	A436-20- ② -2- WT NT	42W	4000K	1400mA	6600Lm	61%


220 V~ | IP20 | CRI>90 | L80B10 >60.000 h | MacAdam Step 2 | INCL | OPTIONS* | 2m | FAST | Ø62 | 100°

		P	CCT	I	Flux	LOR
LINE Suspension 1500 Base	A436-11- ② -0- WT NT	31,5W	2700K	1050mA	4500Lm	61%
	A436-11- ② -1- WT NT	31,5W	3000K	1050mA	4800Lm	61%
	A436-11- ② -2- WT NT	31,5W	4000K	1050mA	4950Lm	61%
LINE Suspension 2000 Base	A436-21- ② -0- WT NT	42W	2700K	1400mA	6000Lm	61%
	A436-21- ② -1- WT NT	42W	3000K	1400mA	6400Lm	61%
	A436-21- ② -2- WT NT	42W	4000K	1400mA	6600Lm	61%


220 V~ | IP20 | CRI>90 | L80B10 >60.000 h | MacAdam Step 2 | INCL | OPTIONS* | 2m | FAST | 100°

② *OPTIONS

1	No DIM
2	DIM DALI
3	DIM Push



LINE SUSPENSION 1500 BASE / 2000 BASE



COLOUR | WT | NT | W | N | MATERIAL | AL | PC |

» PLEASE CONSULT



RCE Arquitectes | Styling: Magda Martínez | Photography: Egidio Pons




OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Coaxial Trimless


A023-00-03- | W | N |



FASTENING

Steel Cable Trimless

A023-00-05- | W | N |



COAXIAL TRIMLESS



STEEL CABLE TRIMLESS



		P	CCT	I	Flux Up	Flux Down	LOR
LINE Suspension Direct & Indirect 1500	A437-10- ② -0- WT NT	35W	2700K	1200mA	2100Lm	3120Lm	61%
	A437-10- ② -1- WT NT	35W	3000K	1200mA	2140Lm	3210Lm	61%
	A437-10- ② -2- WT NT	35W	4000K	1200mA	2250Lm	3360Lm	61%
LINE Suspension Direct & Indirect 2000	A437-20- ② -0- WT NT	41W	2700K	1400mA	2030Lm	4060Lm	61%
	A437-20- ② -1- WT NT	41W	3000K	1400mA	2080Lm	4160Lm	61%
	A437-20- ② -2- WT NT	41W	4000K	1400mA	2180Lm	4370Lm	61%



220 V~ | IP20 | CRI>90 | L80B10 >60.000 h | MacAdam Step 2 | INCL | OPTIONS* | CABLE 2 m | FAST | Ø62 | 100°

		P	CCT	I	Flux Up	Flux Down	LOR
LINE Suspension Direct & Indirect 1500 Base	A437-11- ② -0- WT NT	35W	2700K	1200mA	2100Lm	3120Lm	61%
	A437-11- ② -1- WT NT	35W	3000K	1200mA	2140Lm	3210Lm	61%
	A437-11- ② -2- WT NT	35W	4000K	1200mA	2250Lm	3360Lm	61%
LINE Suspension Direct & Indirect 2000 Base	A437-21- ② -0- WT NT	41W	2700K	1400mA	2030Lm	4060Lm	61%
	A437-21- ② -1- WT NT	41W	3000K	1400mA	2080Lm	4160Lm	61%
	A437-21- ② -2- WT NT	41W	4000K	1400mA	2180Lm	4370Lm	61%

220 V~ | IP20 | CRI>90 | L80B10 >60.000 h | MacAdam Step 2 | INCL | OPTIONS* | CABLE 2 m | FAST | 100°


② *OPTIONS

1	No DIM
2	DIM DALI
3	DIM Push



COLOUR | WT | NT | W | N | MATERIAL | AL | PC |

«» » PLEASE CONSULT




OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Coaxial Trimless


A023-00-03- | W | N |



FASTENING

Steel Cable Trimless

A023-00-05- | W | N |



COAXIAL TRIMLESS



STEEL CABLE TRIMLESS



		P	CCT	I	Flux	LOR
LINE Micro Suspension 1400	A438-10- Ⓢ -0- WT NT	13,5W	2700K	350mA	2160Lm	66%
	A438-10- Ⓢ -1- WT NT	13,5W	3000K	350mA	2200Lm	66%
LINE Micro Suspension 2000	A438-20- Ⓢ -0- WT NT	18W	2700K	700mA	2860Lm	66%
	A438-20- Ⓢ -1- WT NT	18W	3000K	700mA	3000Lm	66%

220
240 V~ |  IP20 | CRI>90 | L80B10
>40.000 h

 MacAdam
Step 2

 INCL

 OPTIONS*

 CABLE
2 m

 FAST

 Ø50

 105°

		P	CCT	I	Flux	LOR
LINE Micro Suspension 1400 Base	A438-11- Ⓢ -0- WT NT	13,5W	2700K	350mA	2160Lm	66%
	A438-11- Ⓢ -1- WT NT	13,5W	3000K	350mA	2200Lm	66%
LINE Micro Suspension 2000 Base	A438-21- Ⓢ -0- WT NT	18W	2700K	700mA	2860Lm	66%
	A438-21- Ⓢ -1- WT NT	18W	3000K	700mA	3000Lm	66%

220
240 V~ |  IP20 | CRI>90 | L80B10
>40.000 h

 MacAdam
Step 2

 INCL

 OPTIONS*



 CABLE
2 m

 FAST

 105°

Ⓢ *OPTIONS

1	No DIM
2	DIM DALI
3	DIM Push



COLOUR | WT  | NT  | W  | N  | MATERIAL |  AL |  PC |

BLACK FOSTER SUSPENSION



○	BEAM	LOR
0	38°	92%
1	19°	90%

⊞	*OPTIONS
1	No DIM
2	DIM DALI
3	DIM Push
5	DIM On Board

MAINS TRIMLESS



MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS



		P	CCT	I	Flux
BLACK FOSTER Suspension 1200	A321-1- ○ - ⊞ -0- WT NT WTMG NTMG	21W	2700K	700mA	1900Lm
	A321-1- ○ - ⊞ -1- WT NT WTMG NTMG	21W	3000K	700mA	2100Lm
	A321-1- ○ - ⊞ -2- WT NT WTMG NTMG	21W	4000K	700mA	2500Lm
BLACK FOSTER Suspension 1600	A321-2- ○ - ⊞ -0- WT NT WTMG NTMG	31,5W	2700K	700mA	2850Lm
	A321-2- ○ - ⊞ -1- WT NT WTMG NTMG	31,5W	3000K	700mA	3150Lm
	A321-2- ○ - ⊞ -2- WT NT WTMG NTMG	31,5W	4000K	700mA	3750Lm

220 V~ | IP20 | CRI>90 | L80B10 > 60.000 h

MacAdam Step 3 | INCL | OPTIONS* | 2 m | FAST | UGR <19 | 38° / 19°

OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Mains Trimless

A023-00-01- | W | N | NO DIM On Board

Mains Thick Trimless

A023-00-02- | W | N | DALI | Push





FASTENING

Steel Cable Trimless



A023-00-05- | W | N | 2 Pcs. needed



BLACK FOSTER SUSPENSION 1200



BLACK FOSTER SUSPENSION 1600



COLOUR | WT | NT | WTMG | NTMG | W | N | MATERIAL | AL | ABS+PC |

TO ACHIEVE A HOMOGENEOUS LIGHT DISTRIBUTION, A DISTANCE OF 80 CM BETWEEN THE LUMINAIRE AND THE WORK SURFACE IS RECOMMENDED. » PLEASE CONSULT

WIRE TRIMLESS ACCESSORY

SLIMGOT



COAXIAL TRIMLESS



		P	CCT	I	Flux	LOR
SLIMGOT 120	A203-1- Ⓞ -01- WT NT	14,8W	3000K	500mA	2360Lm	85%
	A203-1- Ⓞ -02- WT NT	14,8W	4000K	500mA	2400Lm	85%
SLIMGOT 150	A203-2- Ⓞ -01- WT NT	21W	3000K	700mA	3300Lm	85%
	A203-2- Ⓞ -02- WT NT	21W	4000K	700mA	3350Lm	85%

220
240 V~

 IP20

CRI>90

L80B10
>60.000 h

 MacAdam
Step 2

 INCL

 OPTIONS*

 CABLE
2 m

 FAST

 86°

Ⓞ	*OPTIONS
1	No DIM
2	DIM DALI / Push

OPTIONAL ACCESSORY

WIRE TRIMLESS Accessory



Coaxial Trimless A023-00-03- | W | N |

Feeding: Only 1 piece needed.
Fasteners not available

 REMOTE

 INCL

 Ø20



COLOUR | WT  | NT  | W  | N  | MATERIAL | AL  | PMMA  |

» PLEASE CONSULT

WIRE TRIMLESS ACCESSORY

FIFTY+ SUSPENSION



Casa MAX12, Valencia (Spain) | DG Arquitecto Valencia | Photography: Mariela Apollonio



OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED


Mains Trimless

A023-00-01- | W | N |



Mains Thick Trimless


A023-00-02- | W | N |



FASTENING

Steel Cable Trimless*

A023-00-05- | W | N |



MAINS TRIMLESS



MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS




		P	CCT	I	Flux	LOR	L
FIFTY + Suspension 100	A446-01- Ⓞ -1- WT NT	15,4W	3000K	700mA	2280Lm	70%	1010mm
	A446-01- Ⓞ -2- WT NT	15,4W	4000K	700mA	2400Lm	70%	1010mm
FIFTY + Suspension 150	A446-02- Ⓞ -1- WT NT	23,1W	3000K	700mA	3420Lm	70%	1510mm
	A446-02- Ⓞ -2- WT NT	23,1W	4000K	700mA	3600Lm	70%	1510mm
FIFTY + Suspension 200	A446-03- Ⓞ -1- WT NT	30,8W	3000K	700mA	4560Lm	70%	2010mm
	A446-03- Ⓞ -2- WT NT	30,8W	4000K	700mA	4800Lm	70%	2010mm
FIFTY + Suspension 300	A446-04- Ⓞ -1- WT NT	46,2W	3000K	700mA	6840Lm	70%	3010mm
	A446-04- Ⓞ -2- WT NT	46,2W	4000K	700mA	7200Lm	70%	3010mm
FIFTY + H0 Suspension 100	A446-11- Ⓞ -1- WT NT	23,6W	3000K	1050mA	3260Lm	70%	1010mm
	A446-11- Ⓞ -2- WT NT	23,6W	4000K	1050mA	3440Lm	70%	1010mm
FIFTY + H0 Suspension 150	A446-12- Ⓞ -1- WT NT	35,4W	3000K	1050mA	4890Lm	70%	1510mm
	A446-12- Ⓞ -2- WT NT	35,4W	4000K	1050mA	5160Lm	70%	1510mm
FIFTY + H0 Suspension 200	A446-13- Ⓞ -1- WT NT	47,2W	3000K	1050mA	6520Lm	70%	2010mm
	A446-13- Ⓞ -2- WT NT	47,2W	4000K	1050mA	6880Lm	70%	2010mm
FIFTY + H0 Suspension 300	A446-14- Ⓞ -1- WT NT	70,8W	3000K	1050mA	9780Lm	70%	3010mm
	A446-14- Ⓞ -2- WT NT	70,8W	4000K	1050mA	10320Lm	70%	3010mm

220 V~ | IP20 | CRI>90 | L80B10 > 60.000h | MacAdam Step 2 | OPTIONS* | CABLE 2 m | FAST | INCL | DIFFUSER | FAST | CONNEC | INCL | 104°

		P	CCT	I	Flux	LOR	L
FIFTY + UGR Suspension 100	A446-21- Ⓞ -1- WT NT	15,4W	3000K	700mA	2280Lm	47%	1010mm
	A446-21- Ⓞ -2- WT NT	15,4W	4000K	700mA	2400Lm	47%	1010mm
FIFTY + UGR Suspension 150	A446-22- Ⓞ -1- WT NT	23,1W	3000K	700mA	3420Lm	47%	1510mm
	A446-22- Ⓞ -2- WT NT	23,1W	4000K	700mA	3600Lm	47%	1510mm
FIFTY + UGR Suspension 200	A446-23- Ⓞ -1- WT NT	30,8W	3000K	700mA	4560Lm	47%	2010mm
	A446-23- Ⓞ -2- WT NT	30,8W	4000K	700mA	4800Lm	47%	2010mm
FIFTY + UGR Suspension 300	A446-24- Ⓞ -1- WT NT	46,2W	3000K	700mA	6840Lm	47%	3010mm
	A446-24- Ⓞ -2- WT NT	46,2W	4000K	700mA	7200Lm	47%	3010mm
FIFTY + UGR H0 Suspension 100	A446-31- Ⓞ -1- WT NT	23,6W	3000K	1050mA	3260Lm	47%	1010mm
	A446-31- Ⓞ -2- WT NT	23,6W	4000K	1050mA	3440Lm	47%	1010mm
FIFTY + UGR H0 Suspension 150	A446-32- Ⓞ -1- WT NT	35,4W	3000K	1050mA	4890Lm	47%	1510mm
	A446-32- Ⓞ -2- WT NT	35,4W	4000K	1050mA	5160Lm	47%	1510mm
FIFTY + UGR H0 Suspension 200	A446-33- Ⓞ -1- WT NT	47,2W	3000K	1050mA	6520Lm	47%	2010mm
	A446-33- Ⓞ -2- WT NT	47,2W	4000K	1050mA	6880Lm	47%	2010mm
FIFTY + UGR H0 Suspension 300	A446-34- Ⓞ -1- WT NT	70,8W	3000K	1050mA	9780Lm	47%	3010mm
	A446-34- Ⓞ -2- WT NT	70,8W	4000K	1050mA	10320Lm	47%	3010mm

220 V~ | IP20 | CRI>90 | L80B10 > 60.000h | MacAdam Step 2 | OPTIONS* | CABLE 2 m | FAST | INCL | UGR DIFFUSER | FAST | CONNEC | INCL | UGR <19 | 62°

Ⓞ	*OPTIONS
1	No DIM
2	DIM DALI
3	DIM Push



COLOUR | WT ☐ | NT ☒ | W ☐ | N ☒ | MATERIAL | ☒ AL | ☐ PC |

* AS MANY PIECES AS NEEDED ACCORDING TO YOUR PRODUCT

MINIMAL TRACK SUSPENSION




OPTIONAL ACCESSORIES




WIRE TRIMLESS Accessories

Coaxial Trimless A023-00-03- | W | N |

FASTENERS NOT AVAILABLE.



COAXIAL TRIMLESS



MINIMAL TRACK 24V Suspension

Profile 2m

A384-02-00- | N |

Profile 2m Initial feed kit

A400-02-10- | N |

Profile 2m Middle feed kit*


A400-02-20- | N |

* Unidirectional Middle Feed.

MINIMAL TRACK 24V Suspension Corner 90°

A400-00-03- | N |

Cable Length = 85mm.



MINIMAL TRACK 24V Suspension

Rubber Cable n x 1m

A400-00-01- | N |

n = Total Length of System.

24 V | Max. 4A | III

MINIMAL TRACK 24V Suspension Straight Joiner

A400-00-02- | N |


MINIMAL TRACK 24V Suspension Kit

A400-02-04- | N |

MINIMAL TRACK 24V Suspension End Caps

A400-00-05- | N |

Two End Caps Included





			P	V	D (A x B x C)
MINIMAL TRACK 24V Suspension Power Supply Box	ON/OFF	A400-00-06- NT	40W	24V	280 x 30 x 36mm
		A400-00-07- NT	100W	24V	280 x 30 x 36mm
220 V~ Included ON/OFF 24Vdc Power Supply.					
MINIMAL TRACK 24V Remote Power Supply	ON/OFF	0434-01-37	60W	24V	180 x 52 x 30mm
		0433-10-22	100W	24V	295 x 43 x 30mm
220 V~					
MINIMAL TRACK 24V Remote Constant Voltage Dimmer		0433-01-32	DALI / Push	24V	181 x 42 x 20mm
		0433-01-33	CASAMBI	24V	172 x 42 x 20mm
		0434-01-64	WIFI	24V	105 x 44 x 23mm

24 V

DROP VOLTAGE TABLE

POWER [W]	CABLE SECTION [mm²]	CABLE LENGTH [m]			
		<5	<10	<20	<30
40	0,75	30	30	30	30
	1,5	30	30	30	30
60	0,75	30	30	20	10
	1,5	30	30	30	20
100	0,75	20	10	X	X
	1,5	20	20	10	X




COLOUR | N ■ | NT ■ |

RAL ⓘ » 538

DIM OPTIONS PLEASE CONSULT


TRACK 48V




TRACK 48V SURFACE

TRACK 48V SURFACE 1m	A338-11-00-	NT	WT
TRACK 48V SURFACE 2m	A338-12-00-	NT	WT
TRACK 48V SURFACE 3m	A338-13-00-	NT	WT
TRACK 48V SURFACE Corner 90° One Plane	A338-14-00-	NT	WT

TRACK 48V SURFACE
Corner 90° One Plane




*Electrical connection not included



TRACK 48V SURFACE SHORT

TRACK 48V SURFACE SHORT 1m	A338-21-00-	NT	WT
TRACK 48V SURFACE SHORT 2m	A338-22-00-	NT	WT
TRACK 48V SURFACE SHORT 3m	A338-23-00-	NT	WT
TRACK 48V SURFACE SHORT Corner 90° One Plane	A338-24-00-	NT	WT



TRACK 48V SURFACE SHORT
Corner 90° One Plane



*Electrical connection not included

		P	V
CONSTANT VOLTAGE LED POWER SUPPLY	0434-01-62	150W	48V

220
240 V~ | DRIVER MUST BE PLACED ON REMOTE




DROP VOLTAGE TABLE

		CABLE LENGHT (m)			
		5	10	20	30
POWER (W)	CABLE SECTION (mm²)	TRACK LENGHT (m)			
		50	50	X	X
100	0,75	50	50	X	X
	1,5	50	50	40	25
150	0,75	40	15	X	X
	1,5	50	40	20	X

ACCESSORIES

TRACK 48V

ALL 48V TRACKS




TRACK 48V Live-End Connector
A338-00-01- N W

TRACK 48V Corner Connector
A338-00-12- N W

TRACK 48V Corner 90° Connector One Plane
A338-00-24- N W

*Not suitable for trimless version



TRACK 48V Central Connector
A338-00-02- N W

TRACK 48V Wireless Control
0434-01-31- N W Casambi/AAG Stucchi App




ACCESSORIES

TRACK 48V

SUSPENSION & SUSPENSION SHORT 48V



TRACK 48V SURFACE Suspension Kit (2 units)
A338-00-15- NT WT



TRACK 48V SURFACE Suspension Feed Kit
A338-00-16- N W NO DIM
A338-00-17- N W DIM

*For remote power supply


TRACK 48V Wired Power Supply Case
A338-00-25- NT WT 150W NO DIM
A338-00-26- NT WT 150W DIM




INCL

WIRE TRIMLESS ACCESSORIES

FEED
Mains Trimless*
A023-00-01- W N NO DIM
Mains Thick Trimless*
A023-00-02- W N DIM



FASTENING
Steel Cable Trimless*
A023-00-05- W N



TRIMLESS, SURFACE & SUSPENSION 48V


TRACK 48V TRIMLESS & SURFACE End
A338-00-06- NT WT

TRACK 48V TRIMLESS & SURFACE End Feed
A338-00-07- NT WT

SURFACE SHORT & SUSPENSION SHORT 48V

TRACK 48V SURFACE SHORT End
A338-00-18- NT WT

TRACK 48V SURFACE SHORT End Feed
A338-00-19- NT WT




COLOUR | N ■ | W □ | NT ■ | WT □ |

* AS MANY PIECES AS NEEDED ACCORDING TO YOUR PRODUCT

WIRE TRIMLESS ACCESSORY

BLACK FOSTER

CUSTOM SURFACE




BLACK FOSTER Custom Surface 1m	A452-01-00- NT WT
BLACK FOSTER Custom Surface 2m	A452-02-00- NT WT
BLACK FOSTER Custom Surface 3m	A452-03-00- NT WT



BLACK FOSTER Custom Surface L-Joint	A452-04-00- NT WT
BLACK FOSTER Custom Surface T-Joint	A452-05-00- NT WT
BLACK FOSTER Custom Surface X-Joint	A452-06-00- NT WT






			L	
BLACK FOSTER Custom Surface Gap 250	A452-00-01- N	250mm		
BLACK FOSTER Custom Surface Gap 500	A452-00-02- N	500mm		



DROP VOLTAGE TABLE


POWER (W)	CABLE SECTION (mm²)	CABLE LENGTH (m)				TRACK LENGTH (m)
		5	10	20	30	
100	0,75	50	50	X	X	
	1,5	50	50	40	25	
150	0,75	40	15	X	X	
	1,5	50	40	20	X	



COLOUR | NT ■ | WT □ | N ■ |

BLACK FOSTER SURFACE CUSTOM


L-JOINT



Electrical connection not included

BLACK FOSTER SURFACE CUSTOM


T-JOINT



Electrical connection not included

BLACK FOSTER SURFACE CUSTOM




X-JOINT



Electrical connection not included

		P	V	D (A x B x C)
CONSTANT VOLTAGE LED POWER SUPPLY	0434-01-61*	100W	48V	198 x 16 x 19mm
	0434-01-62	150W	48V	350 x 30 x 18mm


220 V~ | *To be installed inside the track.




» PLEASE CONSULT



JUMA architects | Susana Ocaña | Photography: Eugeni Pons




Live-End Connector
A338-00-01- N
Central Connector
A338-00-02- N
L-Joint Connector
A338-00-12- N
T-Joint Connector
A450-00-07- N
X-Joint Connector
A450-00-08- N




BLACK FOSTER Custom Surface
End A452-00-03- N W
BLACK FOSTER Custom Surface
End Feed A452-00-04- N W
BLACK FOSTER Custom Surface
Straight Joiner A452-00-05

SUSPENSION COMPONENTS



Wired Power Supply Case 48V
A338-00-25- NT WT 150W NO DIM
A338-00-26- NT WT 150W DIM
220 V ~ 240 INCL



Suspension Feed Kit
A338-00-16- N W NO DIM
A338-00-17- N W DIM
For remote power supply
A338-00-27- N W NO DIM
A338-00-28- N W DIM
For power supply inside the track

BLACK FOSTER Custom Surface
Suspension Kit (2 units)
A450-00-09- NT WT
Suggested mounting accessories quantities: 1000mm - 2 Pcs. 2000mm - 2 Pcs. 3000mm - 3 Pcs.

MAINS TRIMLESS



MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS



WIRE TRIMLESS ACCESSORIES

FEED
Mains Trimless*
A023-00-01- W N NO DIM
Mains Thick Trimless*
A023-00-02- W N DIM
Ø15 15 MIN.35
REMOTE INCL Ø20



FASTENING
Steel Cable Trimless*
A023-00-05- W N
Ø15 15 MIN.20
INCL Ø20


COLOUR N ■ W □ NT ■ WT □
* AS MANY PIECES AS NEEDED ACCORDING TO YOUR PRODUCT

WIRE TRIMLESS ACCESSORY

BLACK FOSTER

MICRO CUSTOM SURFACE





A 3D perspective diagram of a U-shaped channel. A dimension line above the channel indicates its length, labeled with the letter L .

MAX 2000 mm

220 V~
240

48Vdc POWER SUPPLY

CABLE LENGHT = 2,5 m

LIVE END

TRACK LENGHT

L (m)

REMOTE 48Vdc POWER SUPPLY

CABLE LENGHT = 2,5 + L

MAX 2000 mm

220 V~
240


CABLE LENGHT = 0 m

48Vdc POWER SUPPLY*


LIVE END

TRACK LENGHT


RAL ⓘ » 538



Electrical connection not included







Electrical connection not included




Electrical connection not included

220 V~ | *To be installed inside the track.



220
240 V~  INCL



Suggested mounting accessories quantities:
1000mm - 2 Pcs.
2000mm - 2 Pcs.
3000mm - 3 Pcs.

For remote power supply

For power supply inside the track

[illegible]

Technical drawing of a square nut. The drawing shows a square nut with a height of 15 and a width of MIN.20. The material is INCL. The drawing includes a cross-section view showing a hole with a diameter of Ø15.

RAL ⓘ » 538

Glossar

P	Leistung		CE-gekennzeichnet
CCT	Farbtemperatur		ENEC-Zertifizierung
I	Stromstärke		Klasse I
Flux	Bruttolichtstrom		Klasse II
L	Länge (in mm).		Klasse III
LOR	Zusammenhang zwischen dem Ausgangsstrom der Leuchte und dem Ausgangsstrom der Lichtquelle		Farbstabilität: MacAdam Stufen
IPXX	Schutzgrad gegen Eindringen von Staub und Feuchtigkeit		Dimmbar
BEAM	Abstrahlwinkel		Vorschaltgerät elektronische inklusive
CRI	Farbwiedergabeindex		Komponenten für Fernbedienung
AL	Aluminium		Einbauloch in mm
PC	Polycarbonat		Schnellsteckeranschluss
BR	Messing		Hängekabel
ABS	Acrylnitril-Butadien-Styrol		Schnelle Regulation del Hängekabels
PMMA	Polymethylmetacrylat		Trimless Zubehör
TRANS	Transparent		Diffusor
D	Abmessungen (in mm)		Diffusor
V	Spannungsversorgung Ausgang Volt		Steuerung über Bluetooth
220 V~ 240	Netzspannung 220-240V		Art und Ausrichtung des Lichtkegels
48 V	Netzspannung 48vdc		Sehkomfort. UGR (<i>Unified Glare Rating</i>)
24 V	Netzspannung 24vdc		Hergestellt aus
	LED-Lampe		Reflektor

Farben

Die für jeden Artikelcode angegebenen Beleuchtungswerte entsprechen den Ergebnissen, die anhand der ersten in der Aufstellung enthaltenen Farbe ermittelt wurden.

	N Schwarz matt = RAL 9005		MG Metallisiertes Gold**
	NT Schwarz Feinstruktur = RAL 9005		MC Metallisiertes Kupfer**
	W Weiß = RAL 9016		BG Gebürstetes Gold**
	WT Weiß Feinstruktur = RAL 9016		BC Gebürstetes Kupfer**
	O Orange = RAL 7022*		WTMG Weiß Feinstruktur - Metallisiertes Gold**
	R Rot = RAL 3018*		NMG Schwarz matt - Metallisiertes Gold**
	G Gold = RAL 1036*		NTMG Schwarz Feinstruktur - Metallisiertes Gold**

* Farbe in der Serie ähnlich RAL.
** RAL nicht verfügbar. Metallic-Finish.

ARKOSLIGHT®

Calle N · Pol. Ind. EL OLIVERAL
46394 Ribarroja del Turia · Valencia (Spain)
Tel. +34 961 667 207 · Fax +34 961 667 054
info@arkoslight.com · www.arkoslight.com
France: +33 182 885 200 · Italia: +39 02 9475 0007
Deutschland: +49 22 182 829 313



LIGHT&LIFE

DESDE 1984